


# UL 1332

## Application

The product is suitable for home appliances, lighting, electronic equipment temperature sensor cable.



**Product structure diagram**

## Executive Standard

UL 758.

## Technical parameters

Rated voltage	600V
Conductor	Stranded or Solid Tinned copper accordng IEC 60228 class 5
Insulation	FEP
Temperature range	-80°C~/200°C
Min bending radius	One time:5xCable diameter
	Repeated:10xCable diameter

Teflon self-extinguishing and flame retardant, test method according to UL 1581,IEC 60332,IEC 60331.

# LIAONING CREATE CABLE CO.,LTD.

## Specification range

Item number	Cores x AWG	Conductor structure (number x diameter)	Reference Overall Diameter mm	Package Length (m)
1093001	1x10	37x0,43	3,7	305
1093002	1x12	19x0,48	3,1	
1093003	1x14	19x0,37	2,6	
1093004	1x16	19x0,30	2,2	
1093005	1x17	19x0,26	2,0	
1093006	1x18	19x0,23	1,8	
1093007	1x20	19x0,19	1,6	
1093008		1x0,82	1,5	
1093009	1x22	19x0,15	1,4	
1093010		1x0,65	1,3	
1093011	1x24	7x0,20	1,3	
1093012		1x0,50	1,2	
1093013	1x26	7x0,16	1,1	
1093014		1x0,41	1,1	
1093015	1x28	7x0,12	1,0	
1093016		1x0,32	1,0	
1093017	1x30	7x0,10	0,9	
1093018		1x0,254	0,9	

