


UL 1723

Application

The product is suitable for home appliances, lighting, electronic equipment temperature sensor cable.



Product structure diagram

Executive Standard

UL 758.

Technical parameters

Rated voltage	300V
Conductor	Stranded or Solid Tinned copper IEC 60228 class 5
Insulation	FEP
Temperature range	-80°C~/200°C
Min bending radius	One time:5xCable diameter
	Repeated:10xCable diameter
Teflon self-extinguishing and flame retardant, test method according to UL 1581,IEC 60332,IEC 60331.	

Specification range

Item number	Cores x AWG	Conductor structure (number x diameter)	Reference Overall Diameter mm	Package Length (m)
1094001	1x16	19x0,30	2,0	305
1094002	1x17	19x0,26	1,8	
1094003	1x18	19x0,23	1,7	
1094004	1x20	19x0,19	1,6	
1094005		1x0,80	1,3	

LIAONING CREATE CABLE CO.,LTD.

Specification range

Item number	Cores x AWG	Conductor structure (number x diameter)	Reference Overall Diameter mm	Package Length (m)
1094006	1x22	19x0,16	1,3	610
1094007		1x0,65	1,2	
1094008	1x24	7x0,20	1,1	
1094009		1x0,50	1,0	
1094010	1x26	7x0,16	1,0	
1094011		1x0,40	0,9	
1094012	1x28	7x0,12	0,9	
1094013		1x0,32	0,8	
1094014	1x30	7x0,10	0,8	
1094015		1x0,254	0,8	
1094016	1x32	7x0,08	0,8	
1094017		1x0,20	0,7	

